

CVD Series

Card Dispenser

- Easy card filling
- Multi-inteface: Pulse, Hopper, RS232
- 12V and 24V DC power acceptable
- Card capacity of 300 to 1000 cards
- Standard type and drop type card dispenser available
- Low level sensor function(optional)



ICT

CVD Series

Card Dispenser

CVD series is a card vending dispenser which is base on the design of CVD series.

The machine features low level sensor function with Standard type or Drop type as reliable card dispenser which is able to work steadily and fast approx 1 second per card.

Specifications



Card Dispensing Speed

Approx. 1 sec.



Interface

Hopper, Pulse, RS232



Applicable Cards

Length : 76~90mm ±0.5mm
Width : 53~58mm ±0.5mm
Thickness: 0.2~1mm (Max.)



Card Capacity

CVD-300 Series: Approx. 300 cards
CVD-1000 Series: Approx. 1000 cards
(a card thickness of 0.35mm)



Power Source

12V DC (11.4V~12.6V DC)
24V DC (22.8V~25.2V DC)



Power Consumption

12V DC- Standby: 0.5A, 6W
Operation: 1.25A, 15W
Maximum: 2.5A, 30W
24V DC- Standby: 0.16A, 4W
Operation: 0.83A, 20W
Maximum: 1.66A, 40W



Dimension

445 x 166.2 x 100 mm/
17.53 x 6.54 x 3.94 inches



Weight

CVD- 300 Series: Approx. 1.9 kg
CVD-1000 Series: Approx. 3.2 kg




Environmental

Operating Temperature:
-10°C/14°F~40°C/104°F
Storage Temperature:
-20°C/-4°F~70°C/158°F
Humidity: 30%~90RH%
(no condensation)



Recommended Applications

Indoor Gaming, Vending, Kiosk



Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email : sales@ictgroup.com.tw (Product Information)

rma@ictgroup.com.tw (Technical Service)

Website : www.ictgroup.com.tw