

## SCA1 / SCA2

---

# Coin Acceptor

- Quick and high acceptance rate
- Advanced counterfeit detection
- Multiple coin entry selections
- Standard and long bezel available for SCA1



**ICT**

# SCA1/SCA2

## Coin Acceptor

The SCA series coin acceptors are designed for reliability and security. With multiple configurations to support multiple coin insertion or rejection paths, the SCA is suitable for a wide variety of applications. The SCA2 is equipped with advanced coin validating technology to greatly reduce the chance of receiving counterfeit coins.

### Specifications



#### Acceptance Rate

96% or greater



#### Coin Accepted

SCA1:  
Diameter: 17~29 mm/0.67~1.14 inches,  
Thickness: 1.3~3.2 mm/0.05~0.13 inches

SCA2:  
Diameter: 17~28 mm/0.67~1.10 inches,  
Thickness: 1.5~2.4 mm/0.06~0.09 inches



#### Acceptance Speed

SCA1: Up to 2 coins/sec. (ccTalk)  
Up to 3 coins/sec. (Pulse/Parallel)

SCA2: Up to 2 coins/sec.



#### Coin Entry and Reject

Top Entry, Bottom Reject  
Front Entry, Front Reject  
(Standard/ Long bezel)



#### Sorter Availability

SCA1 Top Entry (ccTalk/ Parallel)  
SCA2 Top Entry (12V DC)



#### Interface

SCA1: Parallel, Pulse, Special Pulse,  
ccTalk, RS232

SCA2: Parallel, Pulse, RS232



#### Power Source

12V ~ 24V DC (ccTalk/ Parallel)  
12V DC (Pulse)



#### Power Consumption

SCA1: Standby:  $\leq 0.05A$   
Operation:  $\leq 0.18A$   
Maximum: 0.5A

SCA2: Standby: 0.1A  
Operation: 0.4A  
Maximum: 0.5A



#### Dimension

SCA1/SCA2 Top Entry:  
102.0 x 98.8 x 55.0 mm/  
4.02 x 3.89 x 2.17 inches

SCA1/SCA2 Front Entry:  
120.6 x 122.3 x 61.6 mm/  
4.75 x 4.81 x 2.42 inches

SCA1 Long bezel:  
155 x 124.7 x 59.5 mm/  
6.10 x 4.91 x 2.34 inches



#### Weight

Approx. 0.25 KG/0.55 lbs



#### Environmental

Operating Temperature:  
-10°C/14°F~55°C/131°F

Storage Temperature:  
-25°C/-13°F~70°C/158°F

Humidity: 30%~85%RH  
(no condensation)



#### Recommended Applications

Indoor Gaming, Amusement



Specifications are subject to change without prior notice.



### International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email : sales@ictgroup.com.tw (Product Information)

rma@ictgroup.com.tw (Technical Service)

Website : www.ictgroup.com.tw